# **AFCONA - 2728**



## **Chemical Composition**

Polymeric defoaming agent, silicone-free.

### **Product general description**

It has the properties of anti-foam and deaeration. It is suitable for solvent based systems, such as UPE, coil coatings and can coatings as well as epoxy resins, and etc.

## **Product Properties:**

AFCONA-2728 provide fast deaeration performance in solvent based resin systems, as well as prevent foam formation, meanwhile, gives good leveling effect.

AFCONA-2728 is recommended for applications in coil and can coatings, provides defoaming property and without defect of craters when applied on assembly line, and almost no side effect.

AFCONA-2728 is recommended for the systems as below:

- 1) UPE(SMC/BMC gel coatings and synthetic);
- 2K epoxy resin systems;
- PU and amino baking systems;
- PVC mixture.

It is recommended to evaluate the compatibility with the vanishes as well as the dosage, where high transparency is required.

## **Product Specification**

Non-volatile matter  $38-42\%(150^{\circ}\text{C},0.5\text{h})$ 

Solvent Alkylbenzen/S.B.P solvent

Density  $0.82 - 0.84 \text{g/cm}^3 (20^{\circ}\text{C})$ 

The refractive index 1.462-1.472 (25°C)

62°C Flash point

Appearance Clear to slightly haze liquid( $25^{\circ}$ C)

#### Addition and dosage

0.1-1.0% based on total formulation. In general under normal conditions: 0.2-0.5% based on total formulation.

#### **Incorporation**

AFCONA - 2728 should be pre-mixed with primary ingredients, to improve the efficiency of defoaming and deaeration.

#### **Storage**

AFCONA-2728 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

# **Packaging**

20kg and 160kg non-returnable containers